

SYSTEMS FOR CONTROLLING A DRYING
CYCLE IN A DRYING APPARATUS

Paul France

Arseni Radomyselski

Related Applications

This application claims priority under 35 U.S.C. 119(e) to U.S. Provisional Application Serial Nos. 60/209,468, 60/209,250, 60/209,443 and 60/209,444 all of which were filed on June 5, 2000, and under 35 U.S.C. 119(e) to U.S. Provisional Application Serial No. 60/260,927 filed on January 11, 2001.

Field of the Invention

The present invention relates to systems for controlling a drying cycle in a drying apparatus by monitoring the lipophilic fluid vapor concentration. The systems utilize a gas sensor capable of sensing the concentration of lipophilic fluid vapor in the drying apparatus drum or a combination of sensors/condition detectors, at least one of which is capable of sensing the concentration of lipophilic fluid vapor in the drying apparatus drum.

Background of the Invention

Conventional laundering techniques for the cleaning and treatment of fabric articles such as garments have long involved both traditional aqueous-based washing and a technique commonly referred to as "dry cleaning". Traditional aqueous based washing techniques have involved immersion of the fabric articles in a solution of water and detergent or soap products, followed by rinsing and drying. However, such conventional immersion cleaning techniques have proven unsatisfactory on a wide range of fabric articles that require special handling and/or cleaning methods due to fabric content, construction, etcetera, which may be unsuitable for immersion in water.

Accordingly, "dry cleaning" has been developed. Dry cleaning typically involves the use of non-aqueous, lipophilic fluids as the solvent or solution for cleaning. While the absence of water permits the cleaning of fabrics without the potential disastrous side

effects water may cause, these lipophilic fluids do not perform well on hydrophilic and/or combination soils.

As a result, new methods have been developed wherein a lipophilic fluid is emulsified with water in order to better perform on these hydrophilic and/or combination
5 soils. Along with this development, however, have arisen new problems. First, many lipophilic fluids have established "safe" exposure/inhalation limits. Second, the drying of items cleaned with the lipophilic fluid cannot be done automatically with the use of only a humidity sensor. Third, energy savings could be appreciated if the items to be dried are exposed to heat and tumbling only for time needed to achieve drying. This would also
10 reduce heat and tumbling damage to the items. Lastly, because these lipophilic fluids possess far greater fouling capabilities than water alone as well as potential flash point problems, sensors typically used in clothes dryers may not be suitable for use in lipophilic fluid clothes dryers.

U.S. Patent No. 6,122,480 (herein incorporated by reference) discloses a system
15 for determining drying time in a clothes dryer that utilizes a humidity sensor. However, the present invention is directed to drying lipophilic fluid from fabrics – not water. Further, U.S. Patent No. 4,111,034 (herein incorporated by reference) is directed to an apparatus for monitoring the solvent content of air in association with a dry-cleaning plant. The present invention is directed to detecting levels of several lipophilic fluids,
20 some of which tend to foul sensors, in many environments, including the home.

Accordingly, the need remains for a system that controls a drying cycle in a drying apparatus by utilizing a gas sensor capable of sensing the concentration of lipophilic fluid vapor in the drying apparatus drum or a combination of sensors/condition detectors, at
25 least one of which is capable of sensing the concentration of lipophilic fluid vapor in the drying apparatus drum.

Summary of the Invention

The present invention provides control over a drying cycle in a drying apparatus that utilizes a gas sensor capable of sensing the concentration of lipophilic fluid vapor in
30 the drying apparatus drum or a combination of sensors/condition detectors, at least one of

which is capable of sensing the concentration of lipophilic fluid vapor in the drying apparatus drum.

In a first embodiment, the present invention provides a system for controlling a drying cycle in a drying apparatus, wherein said drying apparatus comprises a lipophilic fluid vapor, a gas sensor capable of sensing the concentration of lipophilic fluid vapor present in said drying apparatus and transmitting a signal representative of the lipophilic fluid vapor concentration such that said drying cycle is controlled.

In a second embodiment, the present invention provides a system for controlling a drying cycle in a drying apparatus comprising, a condition detector and a gas sensor wherein said condition detector is capable of activating said gas sensor and said gas sensor is capable of generating a signal representative of the lipophilic fluid vapor concentration in the dryer such that the drying cycle is controlled.

In a third embodiment, the present invention provides a method for treating fabrics in need of treatment comprising placing said fabrics in a drying apparatus comprising a gas sensor capable of sensing lipophilic fluid vapor concentration within said drying apparatus and transmitting a signal representative of said lipophilic fluid vapor concentration, contacting said fabrics with a lipophilic fluid, and operating said drying apparatus such that the drying cycle is controlled by said gas sensor

These and other aspects, features and advantages will become apparent to those of ordinary skill in the art from the following detailed description and the appended claims. All percentages, ratios and proportions herein are by weight, unless otherwise specified. All temperatures are in degrees Celsius ($^{\circ}$ C) unless otherwise specified. All measurements are in SI units unless otherwise specified. All documents cited are, in relevant part, incorporated herein by reference.

Brief Description of The Drawings

FIG. 1 is a box diagram of a drying time determining system in accordance with one of the embodiments of the present invention.

FIG. 2 shows annotations used in the procedure algorithms.

FIG. 3 is a signal handling procedure 70 including a gas sensor.

FIG. 4 is a signal handling procedure 130 that includes a gas sensor and condition sensors.

5

FIG. 5 is another signal handling procedure 170 that includes the gas sensor, and the condition sensors.

Detailed Description of the Invention

10 Definitions

The term “lipophilic fluid” used herein is intended to encompass any non-aqueous fluid or vapor capable of removing sebum, as qualified by the test described below.

15 The term “fabrics” and “fabric” used herein is intended to mean any article that is customarily cleaned in a water-based laundry process or in a solvent-based dry cleaning process. As such the term encompasses bulk fabrics and fibers, as well as finished articles of clothing, linens, drapery, and clothing accessories. The term also encompasses other items made in whole or in part of fabric, such as tote bags, furniture covers, tarpaulins and the like.

20 The term “condition detector” used herein is intended to mean any detector and/or sensor capable of quantitatively and/or qualitatively measuring some scientific quality. These qualities may include, and are not limited to, time, temperature, fluid flow, and torque. Further, the measure may be of a physical quality within the drying apparatus(e.g., torque on the spinning drum or inlet air temperature), a physical quality of the fabric load to be dried (e.g., mass or time exposed to drying conditions), a physical
25 quality measured on the outside of the drying apparatus (e.g., condensed fluid flow or outlet air temperature), or any combination thereof.

The term “drying apparatus” used herein is intended to mean any apparatus capable of removing fluid from fabrics. The removal means can be temperature change, gas circulation, light introduction, tumbling, agitation, and combinations of any of these
30 means. The term includes an apparatus capable of “dual mode” functions. A “dual

mode" apparatus is one capable of both washing and drying fabrics within the same drum. These apparatus are commercially available.

The term "safe" used herein is intended to mean the established exposure level for any type of human contact. Specifically, lipophilic fluids suitable for use with the present invention may have established exposure level classifications like contact or absorption, inhalation, and ingestion. For lipophilic fluids with established contact and/or inhalation maximum levels, one of the objects of the present invention is to dry fabrics within a drying operation comprising lipophilic fluid vapor to a level at or below the least of the maximum exposure levels for a particular lipophilic fluid. Safe exposure limits for various lipophilic fluids can be found in: American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values (TLVs) for Chemical Substances and Physical Agents" Second Printing, 1995, ISBN 1-882417-11-9 and National Research Council, "Spacecraft Maximum Allowable Concentrations for Selected Airborne Contaminants," Volume 4, Chapter B7, Page 151-173, Published by National Academy Press, 2000, ISBN 0-309-06795-2 (both sources herein incorporated by reference).

Lipophilic Fluid

In general, lipophilic fluid can be fully liquid at ambient temperature and pressure, can be an easily melted solid, e.g., one which becomes liquid at temperatures in the range from about 0 deg. C to about 60 deg. C, or can comprise a mixture of liquid and vapor phases at ambient temperatures and pressures, e.g., at 25 deg. C and 1 atm. pressure. Thus, the essential lipophilic fluid is not a compressible gas such as carbon dioxide. It is preferred that the lipophilic fluid herein be nonflammable or have relatively high flash points and/or low VOC characteristics, these terms having their conventional meanings as used in the dry cleaning industry, to equal or, preferably, exceed the characteristics of known conventional dry cleaning fluids.

Suitable lipophilic fluids herein readily flow and are non-viscous. In general, the lipophilic fluids herein are required to be fluids capable of at least partially dissolving sebum (e.g. body soil) as defined in the test hereinafter. Mixtures of lipophilic fluid are

also suitable, and provided that the requirements of the test are met, the lipophilic fluid can include any fraction of dry-cleaning solvents, especially newer types including non-fluorinated solvents, or perfluorinated amines. Some perfluorinated amines such as perfluorotributylamines while unsuitable for use as lipophilic fluid may be present as one of many possible adjuncts present in the lipophilic fluid. Other suitable lipophilic fluids include diol solvent systems e.g., higher diols such as C6- or C8- or higher diols; organosilicone solvents including both cyclic and acyclic types, and the like; and mixtures thereof.

A preferred group of nonaqueous liquids suitable for incorporation as the major component of the lipophilic fluid includes low-volatility non-fluorinated organics, silicones, especially those other than amino-functional silicones, and mixtures thereof. Low volatility nonfluorinated organics include for example OLEAN® and other polyol esters, or certain relatively nonvolatile biodegradable mid-chain branched petroleum fractions. Suitable silicones for use as a major component, e.g., more than 50%, of the lipophilic fluid include cyclopentasiloxane, sometimes termed "D5", or linear analogs having approximately similar volatility, optionally complemented by other compatible silicones. Suitable silicones are well known in the literature, see, for example, Kirk Othmer's Encyclopedia of Chemical Technology, and are available from a number of commercial sources, including General Electric, Toshiba Silicone, Bayer, and Dow Corning. Other suitable fluids are commercially available from Procter & Gamble or from Dow Chemical and other suppliers. For example one suitable silicone is SF-1528 available from GE silicone fluids. Notably, SF-1528 fluid is 90% cyclopentasiloxane (D5).

Any non-aqueous fluid that is both capable of meeting known requirements for a dry-cleaning fluid (e.g., flash point etc.) and is capable of at least partially dissolving sebum, as indicated by the test method described below, is suitable as a lipophilic fluid herein. The ability of a particular material to remove sebum can be measured by any known technique. As a general guideline, perfluorobutylamine (Fluorinert FC-43®) on its own (with or without adjuncts) is a reference material that, by definition, is unsuitable as the lipophilic fluid herein (it is essentially a non-solvent) while D5 dissolves sebum.

The following is the method for investigating and qualifying other materials, e.g., other low-viscosity, free-flowing silicones, for use as the lipophilic fluid. The method uses commercially available Crisco ® canola oil, oleic acid (95% pure, available from Sigma Aldrich Co.) and squalene (99% pure, available from J.T. Baker) as model soils for sebum. The test materials should be substantially anhydrous and free from any added adjuncts, or other materials during evaluation.

Prepare three vials. Place 1.0 g of canola oil in the first; in a second vial place 1.0 g of the oleic acid (95%), and in a third and final vial place 1.0g of the squalene (99.9%). To each vial add 1 g of the fluid to be tested for lipophilicity. Separately mix at room temperature and pressure each vial containing the lipophilic soil and the fluid to be tested for 20 seconds on a standard vortex mixer at maximum setting. Place vials on the bench and allow settling for 15 minutes at room temperature and pressure. If, upon standing, a single phase is formed in any of the vials containing lipophilic soils, then the fluid qualifies as suitable for use as a "lipophilic fluid" in accordance with the invention. However, if two or more separate layers are formed in all three vials, then the amount of fluid dissolved in the test fluid will need to be further determined before rejecting or accepting the fluid as qualified.

In such a case, with a syringe, carefully extract a 200 microliter sample from each layer in each vial. The syringe-extracted layer samples are placed in GC autosampler vials and subjected to conventional GC analysis after determining the retention time of calibration samples of each of the three models soils and the fluid being tested. If more than 1% of the test fluid by GC, preferably greater, is found to be present in any one of the layers which consists of the oleic acid, canola oil or squalene layer, then the test fluid is also qualified for use as a lipophilic fluid. If needed, the method can be further calibrated using heptacosfluorotributylamine, i.e., Fluorinert FC-43 (fail) and cyclopentasiloxane (pass).

A suitable GC is a Hewlett Packard Gas Chromatograph HP5890 Series II equipped with a split/splitless injector and FID. A suitable column used in determining the amount of lipophilic fluid present is a J&W Scientific capillary column DB-1HT, 30

meter, 0.25mm id, 0.1um film thickness cat# 1221131. The GC is suitably operated under the following conditions:

Carrier Gas: Hydrogen

Column Head Pressure: 9 psi

5 Flows: Column Flow @ ~1.5 ml/min.

Split Vent @ ~250-500 ml/min.

Septum Purge @ 1 ml/min.

Injection: HP 7673 Autosampler, 10 ul syringe, 1ul injection

Injector Temperature: 350 °C

10 Detector Temperature: 380 °C

Oven Temperature Program: initial 60 °C, hold 1 min.

rate 25 °C/min.

final 380 °C hold 30 min.

15 Preferred lipophilic fluids suitable for use herein can further be qualified for use on the basis of having an excellent garment care profile. Garment care profile testing is well known in the art and involves testing a fluid to be qualified using a wide range of garment or fabric article components, including fabrics, threads and elastics used in seams, etc., and a range of buttons. Preferred lipophilic fluids for use herein have an
20 excellent garment care profile, for example they have a good shrinkage or fabric puckering profile and do not appreciably damage plastic buttons.

For purposes of garment care testing or other qualification, e.g., flammability, a lipophilic fluid can be present in a mixture, e.g., with water, at approximately the ratio to be used in the final lipophilic fluid that will come into contact with fabric articles. Certain
25 materials that remove sebum and which otherwise qualify for use as lipophilic fluids, for example, ethyl lactate can be quite objectionable due to its tendency to dissolve buttons. If such a material is to be used in the lipophilic fluid, it will be formulated with water and/or other solvents such that the overall mix is not substantially damaging to buttons. Other lipophilic fluids, D5 for example, meet the garment care requirements

commendably. Some suitable lipophilic fluids may be found in granted U.S. Patent Nos. 5,865,852; 5,942,007; 6,042,617; 6,042,618; 6,056,789; 6,059,845; and 6,063,135.

Lipophilic solvents can include linear and cyclic polysiloxanes, hydrocarbons and chlorinated hydrocarbons. More preferred are the linear and cyclic polysiloxanes and hydrocarbons of the glycol ether, acetate ester, lactate ester families. Preferred lipophilic solvents include cyclic siloxanes having a boiling point at 760 mm Hg. of below about 250°C. Specifically preferred cyclic siloxanes for use in this invention are octamethylcyclotetrasiloxane, decamethylcyclopentasiloxane, and dodecamethylcyclohexasiloxane. Preferably, the cyclic siloxane comprises decamethylcyclopentasiloxane (D5, pentamer) and is substantially free of octamethylcyclotetrasiloxane (tetramer) and dodecamethylcyclohexasiloxane (hexamer).

However, it should be understood that useful cyclic siloxane mixtures might contain, in addition to the preferred cyclic siloxanes, minor amounts of other cyclic siloxanes including octamethylcyclotetrasiloxane and hexamethylcyclotrisiloxane or higher cyclics such as tetradecamethylcycloheptasiloxane. Generally the amount of these other cyclic siloxanes in useful cyclic siloxane mixtures will be less than about 10 percent based on the total weight of the mixture. The industry standard for cyclic siloxane mixtures is that such mixtures comprise less than about 1% by weight of the mixture of octamethylcyclotetrasiloxane.

Accordingly, the lipophilic fluid of the present invention preferably comprises more than about 50%, more preferably more than about 75%, even more preferably at least about 90%, most preferably at least about 95% by weight of the lipophilic fluid of decamethylcyclopentasiloxane. Alternatively, the lipophilic fluid may comprise siloxanes which are a mixture of cyclic siloxanes having more than about 50%, preferably more than about 75%, more preferably at least about 90%, most preferably at least about 95% up to about 100% by weight of the mixture of decamethylcyclopentasiloxane and less than about 10%, preferably less than about 5%, more preferably less than about 2%, even more preferably less than about 1%, most preferably less than about 0.5% to about 0% by weight of the mixture of octamethylcyclotetrasiloxane and/or dodecamethylcyclohexasiloxane.

Adjunct Ingredients

Adjunct materials can vary widely and can be used at widely ranging levels. For example, deterative enzymes such as proteases, amylases, cellulases, lipases and the like as well as bleach catalysts including the macrocyclic types having manganese or similar transition metals all useful in laundry and cleaning products can be used herein at typical or atypical levels. Adjunct materials that are catalytic, for example enzymes, can be used in "forward" or "reverse" modes, a discovery independently useful from the present invention. For example, a lipolase or other hydrolase may be used, optionally in the presence of alcohols as adjuncts, to convert fatty acids to esters, thereby increasing their solubility in the lipophilic fluid. This is a "reverse" operation, in contrast with the normal use of this hydrolase in water to convert a less water-soluble fatty ester to a more water-soluble material. In any event, any adjunct ingredient must be suitable for use in combination with the lipophilic fluid.

The compositions may comprise emulsifiers. Emulsifiers are well known in the chemical art. Essentially, an emulsifier acts to bring two or more insoluble or semi-soluble phases together to create a stable or semi-stable emulsion. It is preferred in the claimed invention that the emulsifier serves a dual purpose wherein it is capable of acting not only as an emulsifier but also as a treatment performance booster. For example, the emulsifier may also act as a surfactant thereby boosting cleaning performance. Both ordinary emulsifiers and emulsifier/surfactants are commercially available.


Some suitable cleaning additives include, but are not limited to, builders, surfactants, enzymes, bleach activators, bleach catalysts, bleach boosters, bleaches, alkalinity sources, antibacterial agents, colorants, perfumes, pro-perfumes, finishing aids, lime soap dispersants, composition malodor control agents, odor neutralizers, polymeric dye transfer inhibiting agents, crystal growth inhibitors, photobleaches, heavy metal ion sequestrants, anti-tarnishing agents, anti-microbial agents, anti-oxidants, anti-redeposition agents, electrolytes, pH modifiers, thickeners, abrasives, divalent or trivalent ions, metal ion salts, enzyme stabilizers, corrosion inhibitors, diamines or polyamines and/or their alkoxylates, suds stabilizing polymers, solvents, process aids, fabric softening agents,

optical brighteners, hydrotropes, suds or foam suppressors, suds or foam boosters, fabric softeners, antistatic agents, dye fixatives, dye abrasion inhibitors, anti-crocking agents, wrinkle reduction agents, wrinkle resistance agents, soil release polymers, soil repellency agents, sunscreen agents, anti-fade agents, and mixtures thereof.

5 The term "surfactant" conventionally refers to materials that are surface-active either in the water, the lipophilic fluid, or the mixture of the two. Some illustrative surfactants include nonionic, cationic and silicone surfactants as used in conventional aqueous detergent systems. Suitable nonionic surfactants include, but are not limited to:


- 10 a) Polyethylene oxide condensates of nonyl phenol and myristyl alcohol, such as in US 4685930 Kasprzak; and
- b) fatty alcohol ethoxylates, $R-(OCH_2CH_2)_aOH$ $a=1$ to 100, typically 12-40, $R=$ hydrocarbon residue 8 to 20 C atoms, typically linear alkyl. Examples polyoxyethylene lauryl ether, with 4 or 23 oxyethylene groups; polyoxyethylene cetyl ether with 2, 10 or 20 oxyethylene groups; polyoxyethylene stearyl ether, with 2, 10, 20, 21 or 100 oxyethylene groups; polyoxyethylene (2), (10) oleyl ether, with 2 or 10 oxyethylene groups. Commercially available examples include, but are not limited to: ALFONIC, BRIJ, GENAPOL, NEODOL, SURFONIC, TRYCOL. See also US 6013683 Hill et al.,.

20 Suitable cationic surfactants include, but are not limited to, dialkyldimethylammonium salts having the formula:




Where each $R'R''$ is independently selected from the group consisting of 12-30 C atoms or derived from tallow, coconut oil or soy, $X=Cl$ or Br , Examples include: 25 didodecyldimethylammonium bromide (DDAB), dihexadecyldimethyl ammonium chloride, dihexadecyldimethyl ammonium bromide, dioctadecyldimethyl ammonium chloride, dieicosyldimethyl ammonium chloride, didocosyldimethyl ammonium chloride, dicoconutdimethyl ammonium chloride, ditallowdimethyl ammonium bromide (DTAB). Commercially available examples include, but are not limited to: ADOGEN, ARQUAD, 30 TOMAH, VARIQUAT. See also US 6013683 Hill et al., .

Suitable silicone surfactants include, but are not limited to the polyalkyleneoxide polysiloxanes having a dimethyl polysiloxane hydrophobic moiety and one or more hydrophilic polyalkylene side chains and have the general formula:



- 5 wherein a + b are from about 1 to about 50, preferably from about 3 to about 30, more preferably from about 10 to about 25, and each R¹ is the same or different and is selected from the group consisting of methyl and a poly(ethyleneoxide/propyleneoxide) copolymer group having the general formula:



- 10 with at least one R¹ being a poly(ethyleneoxide/propyleneoxide) copolymer group, and wherein n is 3 or 4, preferably 3; total c (for all polyalkyleneoxy side groups) has a value of from 1 to about 100, preferably from about 6 to about 100; total d is from 0 to about 14, preferably from 0 to about 3; and more preferably d is 0; total c+d has a value of from about 5 to about 150, preferably from about 9 to about 100 and each R² is the same or
15 different and is selected from the group consisting of hydrogen, an alkyl having 1 to 4 carbon atoms, and an acetyl group, preferably hydrogen and methyl group. Examples of these surfactants may be found in U.S. Patent No.'s 5,705,562 and 5,707,613, both to Hill.

- Examples of this type of surfactants are the Silwet[®] surfactants which are
20 available CK Witco, OSi Division, Danbury, Connecticut. Representative Silwet surfactants are as follows.

Name	Average MW	Average a+b	Average total c
L-7608	600	1	9
L-7607	1,000	2	17
25 L-77	600	1	9
L-7605	6,000	20	99
L-7604	4,000	21	53
L-7600	4,000	11	68
L-7657	5,000	20	76

L-7602

3,000

20

29

The molecular weight of the polyalkyleneoxy group (R^1) is less than or equal to about 10,000. Preferably, the molecular weight of the polyalkyleneoxy group is less than or equal to about 8,000, and most preferably ranges from about 300 to about 5,000. Thus, the values of c and d can be those numbers which provide molecular weights within these ranges. However, the number of ethyleneoxy units ($-C_2H_4O$) in the polyether chain (R^1) must be sufficient to render the polyalkyleneoxide polysiloxane water dispersible or water soluble. If propyleneoxy groups are present in the polyalkyleneoxy chain, they can be distributed randomly in the chain or exist as blocks. Preferred Silwet surfactants are L-7600, L-7602, L-7604, L-7605, L-7657, and mixtures thereof. Besides surface activity, polyalkyleneoxide polysiloxane surfactants can also provide other benefits, such as antistatic benefits, and softness to fabrics.

The preparation of polyalkyleneoxide polysiloxanes is well known in the art. Polyalkyleneoxide polysiloxanes of the present invention can be prepared according to the procedure set forth in U.S. Pat. No. 3,299,112. Another suitable silicone surfactant is SF-1488, which is commercially available from GE silicone fluids.

These and other surfactants suitable for use in combination with the lipophilic fluid as adjuncts are well known in the art, being described in more detail in Kirk Othmer's Encyclopedia of Chemical Technology, 3rd Ed., Vol. 22, pp. 360-379, "Surfactants and Detergent Systems." Further suitable nonionic detergent surfactants are generally disclosed in U.S. Patent 3,929,678, Laughlin et al., issued December 30, 1975, at column 13, line 14 through column 16, line 6.

The adjunct may also be an antistatic agent. Any suitable well-known antistatic agents used in laundering and dry cleaning art are suitable for use in the methods and compositions of the present invention. Especially suitable as antistatic agents are the subset of fabric softeners which are known to provide antistatic benefits. For example those fabric softeners which have a fatty acyl group which has an iodine value of above 20, such as N,N-di(tallowoyl-oxy-ethyl)-N,N-dimethyl ammonium methylsulfate.

However, it is to be understood that the term "antistatic agent" is not to be limited only to this subset of fabric softeners and includes all antistatic agents.

Although the methods and/or compositions utilized in present invention will be described in detail, it should be understood, and one skilled in the art will recognize, that any compositions, processes, and/or apparatus capable of carrying out the invention could be used.

Sensors

Many sensors can operate with the present invention. Listed below are nonlimiting examples of suitable sensors for use in the present invention. The list is not intended to be complete or exhaustive. A list of sensor types and their manufacturers can be found in the trade publication *Sensors*, September 2000, Volume 17, Number 9, pages 27 to 40.

Reactive Sensors

Reactive sensors generate a signal by measuring some aspect of a chemical reaction of the analyte. The analyte may be destroyed in the process. The smallest and cheapest sensors tend to be reactive types.

Electrochemical Sensors -- A more precise term for this type is the "porous-electrode amperometric gas sensor". It is also called a fuel cell sensor. It will respond to gases that can be electrolytically reduced or oxidized on a metallic catalyst such as platinum or gold. Typical gases measured are O₂, CO, NO₂, NO, and H₂S, and organic vapors such as alcohols, aldehydes, or ketones. Typical sensitivities are in the 3-30 PPM range, but some proprietary sensors are capable of detecting as little as 2 PPB of gases such as ozone, NO₂, H₂S or arsine.

Solid State Semiconductor Sensors -- This sensor typically consists of a bead of tin oxide formed around two fine coils of platinum wire. When the bead is heated using one of the coils, the analyzed gas will oxidize on the bead surface, changing the electrical conductivity as measured between the heated and unheated coils. Nearly all oxidizable

gases can be detected on the SSS sensor. Selectivity can be improved slightly by changing the operating temperature and by doping the tin oxide with various elements.

Combustible Gas Sensor -- The electrical resistance of most metals will increase with temperature. The combustible gas sensor consists of little more than a coil of platinum wire that is electrically heated. When gases combust on the surface, some of the heat of combustion is transferred to the wire coil. The increase in coil temperature is reflected as an increase in electrical resistance.

Flame Ionization Detector (FID) -- The FID works by burning the analyte gas in a hydrogen flame. In this environment, organic compounds produce positive ions, which are collected at a cylindrical electrode above the flame. A very small current will be generated between the collector and the metal flame jet. The FID is very sensitive and linear over many orders of magnitude. Because of the needs for hydrogen and a mechanically stable environment for the flame, the resulting instruments are complex, but some companies such as Foxboro have succeeded in making reliable FID instruments. FIDs are nearly nonselective among organic compounds, but they do limit their responses to organic compounds only.

Chemiluminescence -- Certain chemical reactions generate light, which can be measured with great sensitivity. The most common application of chemiluminescence in gas detection is the measurement of nitric oxide by reaction with ozone; measurements of NO can be made down to the parts per trillion.

Physical Property Sensors

Physical property sensors generally leave the analyte gas undisturbed, and measure some property such as absorption of light or thermal conductivity.

Nondispersive Infrared (NDIR) -- These are the simplest of the spectroscopic sensors. The key components are an infrared source, a light tube, an interference (wavelength) filter, and an infrared detector. The gas is pumped or diffuses into the light tube, and the electronics measures the absorption of the characteristic wavelength of light. NDIR sensors are most often used for measuring carbon dioxide. The best of these have sensitivities of 25-50 PPM.

Spectroscopic Sensors -- These use conventional means to generate monochromatic light in the ultraviolet or infrared and to measure its absorption by a gas. An ultraviolet spectrometer, for example, is the 'gold standard' method for measuring ozone. Specific organic compounds can sometimes be individually measured by measuring absorption of infrared light at one or more wavelengths.

Photoacoustic Sensors -- If a short pulse of infrared light is passed through an absorbing gas, the absorbed light energy becomes heat. The sudden expansion of the gas generates a pressure, or acoustic, wave, which can be measured with a microphone. These are a variation of infrared spectroscopic sensors, with an important twist: the PA sensor measures the light absorbed by the sample. This is in contrast to conventional spectroscopy, which measures the light not absorbed. Since photometric error is eliminated, very sensitive detection is possible. These sensors only became practical in recent years, when digital signal processing (DSP) chips became available to distinguish signal from background noise.

Sorption Sensors

Many types of sensors depend on the physical or chemical sorption of the analyte into a coating on the sensing surface. Depending on the device, the sorption phenomenon may be detected by measurement of mass, refractive index, color change, electrical resistance, etc.

Fiber-Optic -- A thin glass or plastic fiber is coated with a thin layer of a compound that will absorb the analyte. When light is passed through the fiber and reflects from its inside surface, some of the light energy extends beyond the surface of the fiber. This effect is known as the evanescent wave, and its influence is usually no more than a few nanometers. A simple surface coating may absorb organic gases, changing its refractive index. The amount of light reflected inside the fiber is changed; this is detected by a receiver at the other end of the fiber from the light source. Other surface coatings may react with the analyte gas and change color, which will affect the spectrum of the reflected light.

Microbalances -- The simplest form of this sensor uses a quartz crystal that is electronically made to vibrate at its natural frequency. The crystal is coated with a material that absorbs the analyte gas. The mass of the coating increases and slows down the natural rate of vibration of the crystal. The resulting frequency shifts can be measured electronically with great sensitivity. The basic microbalance has been elaborated into more sophisticated devices such as SAW (surface acoustic wave) and resonator devices, which are more sensitive than the simple bulk crystal. This class of sensors is sometimes referred to as gravimetric.

Conductive Polymer -- Certain polymers, such as polyanilines and polythiophenes, are electrically conductive. The conductivity changes when the polymers absorb certain gases. The polymers can also be "tuned" to certain compounds by carrying out the polymerization in the presence of the analyte.

Elastomer Chemiresistor Sensors -- These measure the very slight physical expansion of a film of an elastomeric material that occurs when it absorbs a gas. The elastomer, silicone rubber, for example, contains electrically conductive particles such as carbon. The concentration of particles is adjusted so that there are relatively few conducting paths through the elastomer. Slight expansion of the elastomer causes some of these paths to be broken, and the electrical resistance rapidly increases.

Reactive-Gate Semiconductor Devices -- Most active semiconductor devices, such as MOSFET transistors, use voltages directly applied to the gate to control the flow of charge carriers. Chemically sensitive devices, however, use a chemical interaction to change the transconductance.

System

Figure 1 is a box diagram of a drying time determining system **10** in accordance with one of the embodiments of the present invention. System **10** can include one or more condition sensors **20**, a signal processor **30**, a gas sensor (or solvent vapor detector) **40**, a fuzzy logic control system **50**, and a program selector **60**. Items in dotted lines are optional.

In one aspect of the present invention, the drying time determining system **10** comprises a gas sensor **40** and a signal processor **30**. In operation, the gas sensor **40** measures a concentration of lipophilic fluid vapor within a drying apparatus. Once the gas sensor **40** measures a "safe" lipophilic fluid vapor concentration, the gas sensor **40** sends a signal to the signal processor **30** which causes the drying apparatus to cease operating and subsequently permits a user of the drying apparatus to open the drying apparatus and gain access to the internal chamber of the drying apparatus.

In another aspect of the present invention, the system **60** comprises a gas sensor **40**, a signal processor **30** and one or more condition sensors **20** and optionally, but preferably, a fuzzy logic control system **50** and a program selector **60**.

The condition sensor **20** could be a humidity sensor, a mass load sensor, a temperature sensor, a timer, etcetera. The condition sensor **20** is electrically coupled and can transmit a signal to a signal processor **30**. Signal processor **30** is adapted to trigger the gas sensor **40** once a predetermined set point for the condition sensor **20** is reached. The gas sensor **40** then starts tracking the solvent vapor concentration and transmits its readings back to the signal processor **30**. The signal processor **30** can also be coupled to fuzzy logic control system **50**. Fuzzy logic control system **50** utilizes the signal coming from the signal processor **30** and the signal coming from the program selector **60** to estimate the remaining drying time for a particular load of clothes. The program selector **60** can be activated by the user and may reflect parameters such as the type of garments (e.g. silk, cotton, wool, etcetera) to be cleaned. These signals can then be incorporated into a programmed or programmable algorithm of the fuzzy logic control system **50** to determine remaining drying time.

Figure 2 shows annotations used in the procedure algorithms.

Figure 3 schematically illustrates a gas sensor signal handling procedure **70** for use with the drying time determining system of the present invention. The procedure **70** is executed once a drying cycle of the drying apparatus begins (step **80**), preferably by input from a user and through a microprocessor (fuzzy logic controller). When the drying cycle begins, a gas sensor **90** is activated (step **95**), preferably by a microprocessor. The gas sensor **90** generates a signal **S** that represents vapor concentration present in the

drying apparatus (step **90**). A signal processor **100** monitors the gas sensor signal *S*. The signal processor **100** compares the value of *S* to a preset constant threshold value *V* that represents a vapor concentration equal or below the safe exposure limit (step **100**). As long as the vapor concentration in the drying apparatus is greater than the safe exposure limit, the drying cycle continues (step **110**). When the relation of *S* and *V* indicates that the vapor concentration in the drying apparatus is equal or below the safe exposure limit, the signal processor **100** sends a trigger signal to the microprocessor to end drying cycle (step **120**).

Figure 4 schematically illustrates an alternative embodiment of a condition sensor signal handling procedure **130** for use with the drying time determining system of the present invention. The procedure **130** handles condition sensor signals produced by one or more condition sensors **140** and then executes previously described gas sensor signal handling procedure **70**, as illustrated on Figure 3. The purpose of the procedure **130** is to prevent the gas sensor fouling due to excessive concentration of vapor. The procedure **130** is executed once a drying cycle begins, preferably by input from a user and through a microprocessor (fuzzy logic controller) (step **80**). When the drying cycle begins, one or more condition sensors **140** named *A1*, *A2*...*AX* are activated (step 145), preferably by a microprocessor (step **120**). The condition sensors **140** generate a set of signals *C1*, *C2*...*CX* that represent a set of physical conditions such as time, temperature, pressure etc. A signal processor **150** monitors the condition sensors signals and compares the values of *C1*, *C2*...*CX* to corresponding preset constant threshold values *T1*, *T2*...*TX* that represent the set of predetermined physical conditions indicating the safe operation of the gas sensor **90** in Figure 3. As long as the relation of the predetermined combinations of *C1* and *T1*, *C2* and *T2*,...*CX* and *TX* is not met, the drying cycle continues (step **16**). When the above set of relations is achieved, the signal processor **150** sends a trigger signal activating the gas sensor signal handling procedure **70** of Figure 3, preferably via a microprocessor.

Figure 5 schematically illustrates yet another embodiment of a combined gas sensor signal handling procedure **170** for use with the drying time determining system of the present invention. The procedure **170** is designed to: (1) determine the end of drying

(procedure **70**); (2) optionally, prevent gas sensor fouling (procedure **130**); and (3) optionally, prevent reaching a flash point condition whenever a combustible/flammable lipophilic fluid is used (procedure **180**). The procedure **70** is executed, as described in detail in Figure 4, once a drying cycle of the drying apparatus begins (step **80**), preferably by input from a user and preferably through a microprocessor (fuzzy logic controller). After the start of the drying cycle (step **80**), the procedure **130** is executed to determine the physical conditions that will not cause gas sensor fouling. Once the appropriate physical conditions are met, the gas sensor signal handling procedure **70**, as described in detail in Figure 3, is activated. The procedure **70** is similar to the procedure **70** in Figure 3 except that the step **110** is preferably replaced with the flash point procedure **180**. The procedure **180** is executed as long as the step **100** indicates the vapor concentration is above the safe exposure limit. After the signal processor **100** acquires the gas sensor signal S, compares it to the threshold value V, and determines that the vapor concentration in the drying apparatus is above the safe exposure limit, then the flash point procedure **180** is executed. In the flash point procedure **180**, the signal processor **190** forms a set of sensor signals that includes the gas sensor output S, and one or more condition sensors signals C1, C2 ...CX. The condition sensors signals are selected to provide physical conditions that are suited to determine the flash point of the vapor.

In the preferred embodiment, the condition sensor is a temperature sensor. Since the flash point of the vapor is characterized by the amount of vapor and the temperature of the vapor, the combination of the gas sensor and the temperature sensor signals can indicate when the vapor on the drying apparatus is close to reaching the flash point. The signal processor **190** compares the set of the gas sensor and the condition sensors to the corresponding set of threshold values V, T1, T2 ...TX. The threshold values form a “code value” representing the conditions that are of indication that the drying apparatus is approaching the flash point. If the “code value” is not met, the drying cycle continues (step **200**). Once the “code value” is reached, the signal processor **190** sends a trigger signal to the microprocessor to start a cooling cycle (step **210**), since reduction of temperature would move the vapor condition from the flash point. The microprocessor may have a program to perform cooling for some period of time.

One of the systems of the present invention will be capable of automatically ending a drying cycle in a drying apparatus. It will include a lipophilic fluid, vapor, and a gas sensor. The gas sensor should be capable of sensing the concentration of lipophilic fluid vapor present in the drying apparatus and transmitting a signal representative of the lipophilic fluid vapor concentration.

The signal transmitted from the gas sensor will trigger the drying cycle to end. This could occur at a lipophilic fluid vapor concentration of less than about 40 ppm, more preferably at less than about 20 ppm, even more preferably at less than about 15 ppm, and most preferably at less than about 10 ppm. However, one of the objects of the present invention is to automatically end a drying cycle once a "safe" level, if established for the particular lipophilic fluid, is reached. The "safe" level for any lipophilic fluid will be the lowest established exposure level for any type of human exposure. For instance, the established vapor inhalation "safe" limit is 10 ppm for decamethylcyclotetrasiloxane, a preferred lipophilic fluid. Further, if decamethylcyclotetrasiloxane is the lipophilic fluid utilized, vapor concentrations should be at or below 10 ppm before humans should come in contact with the fabrics. Therefore, a gas or vapor sensor used in a drying apparatus should trigger the drying cycle to end when the decamethylcyclotetrasiloxane vapor concentration is at or below 10 ppm.

There are many gas sensors that would be suitable for use with the present invention. The gas sensors can be, but are not limited to, reactive sensors, physical property sensors, sorption sensors, and combination sensors utilizing at least two of the above sensing mechanisms. More specifically, the gas sensors can be, but are not limited to, electrochemical sensors, solid state semiconductor sensors, combustible gas sensors, flame ionization detectors, chemiluminescence sensors, nondispersive infrared sensors, spectroscopic sensors, photoacoustic sensors, fiber-optic sensors, microbalance sensors, conductive polymer sensors, elastomer chemiresistor sensors, reactive-gate semiconductor sensors, and combination sensors utilizing at least two of the above sensor types.

A preferred lipophilic fluid that generates the lipophilic fluid vapor to be sensed by the gas sensor is a linear siloxane, a cyclic siloxane, or a mixture of the two. More specifically, the siloxane can be octamethylcyclotetrasiloxane,

decamethylcyclopentasiloxane, dodecamethylcyclohexasiloxane, or a mixture of at least two. Preferably, decamethylcyclopentasiloxane is the primary lipophilic fluid; and more preferably, the lipophilic fluid is substantially free of octamethylcyclotetrasiloxane.

5 The second system of the present invention will also be capable of automatically ending a drying cycle in a drying apparatus. This system will include a lipophilic fluid vapor to be sensed, a condition detector, and a gas sensor. The condition detector will be capable of activating the gas sensor and the gas sensor will, in turn, generate a signal representative of the lipophilic fluid vapor concentration in the dryer.

10 Once a predetermined lipophilic vapor concentration is reached and a signal representative of that vapor concentration is transmitted, the drying cycle will automatically end. The signal transmitted from the gas sensor will trigger the drying cycle to end. This could occur at a lipophilic fluid vapor concentration of less than about 40 ppm, more preferably at less than about 20 ppm, even more preferably at less than about 15 ppm, and most preferably at less than about 10 ppm. However, one of the objects of
15 the present invention is to automatically end a drying cycle once a "safe" level, if established for the particular lipophilic fluid, is reached. As discussed above, the "safe" level for any lipophilic fluid will be the lowest established exposure level for any type of human exposure.

20 Fouling can be a problem for gas sensors, particularly when siloxane or silicone-based lipophilic fluids are utilized. Siloxanes have a particular tendency to leave a sticky or greasy residue on surfaces. This can occur as a result of lipophilic vapor condensing on a surface, or as a result of lipophilic fluid or vapor coming in contact with a hot surface. Many gas sensors have surfaces that operate at high temperatures and are therefore prone to fouling, particularly in a lipophilic fluid or vapor environment.

25 As such, the second system adds a condition detector to minimize or eliminate the fouling of the gas sensors. It does this by minimizing the total time a gas sensor is exposed to the lipophilic fluid vapor. A physical condition other than lipophilic fluid vapor is measured until the lipophilic fluid vapor concentration is lower. Non-limiting examples of physical conditions that can be measured include time, fabric load mass,
30 temperature, lipophilic fluid flow from said drying apparatus, drying apparatus drum

torque, inlet drying air temperature, outlet drying air temperature, humidity, and combinations of physical conditions.

For example, when a drying cycle is begun, a sensor that detects condensed lipophilic fluid flow from the dryer is automatically turned-on. This physical condition
5 sensor measures condensed lipophilic fluid flow until it is reduced to a predetermined flow rate. Once the lower condensed lipophilic fluid flow rate is detected, the gas sensor is automatically turned-on. Because the gas sensor is "saved" until lipophilic fluid vapor concentrations are lower, the amount of fouling that occurs on the sensor is minimized or eliminated.

10 As in the first system, many gas sensors would be suitable for use with the present invention. They include, but are not limited to, reactive sensors, physical property sensors, sorption sensors, and combination sensors utilizing at least two of the above sensing mechanisms. More specifically, the gas sensors can be, but are not limited to,
15 electrochemical sensors, solid state semiconductor sensors, combustible gas sensors, flame ionization detectors, chemiluminescence sensors, nondispersive infrared sensors, spectroscopic sensors, photoacoustic sensors, fiber-optic sensors, microbalance sensors, conductive polymer sensors, elastomer chemiresistor sensors, reactive-gate semiconductor sensors, and combination sensors utilizing at least two of the above sensor types.

Also as in the first system, the preferred lipophilic fluid to be detected is a linear
20 siloxane, a cyclic siloxane, or a mixture of the two. More specifically, the siloxane can be octamethylcyclotetrasiloxane, decamethylcyclopentasiloxane, dodecamethylcyclohexasiloxane, or a mixture of at least two. Preferably, decamethylcyclopentasiloxane is the primary lipophilic fluid; and more preferably, the lipophilic fluid is substantially free of octamethylcyclotetrasiloxane.

25 It will be understood that the systems of the present invention may be combined with other fabric treatments. For example, prior to the application of the lipophilic fluid, the fabric articles may be subjected to the particulate removal method described in co-
pending application Serial No. 60/191,965, to Noyes et al., filed March 24, 2000, the relevant parts of which are incorporated herein by reference. The systems of the present
30 invention can then be used to help dry the clothes automatically.

The systems of the present invention may be used in a service, such as a dry cleaning service, diaper service, uniform cleaning service, or commercial business, such as a Laundromat, dry cleaner, linen service which is part of a hotel, restaurant, convention center, airport, cruise ship, port facility, casino, or may be used in the home.

5 The systems of the present invention may be performed in an apparatus that is a modified existing apparatus and is retrofitted in such a manner as to conduct the process of the present invention in addition to related processes.

10 The systems of the present invention may also be performed in an apparatus, which is not a modified existing apparatus but is one specifically built in such a manner so as to conduct the present invention or may be added to another apparatus as part of a lipophilic fluid processing system. This would include all the associated plumbing, such as connection to a chemical and water supply, and sewerage for waste wash fluids.

15 The systems of the present invention may be used in an apparatus, which is not a modified existing apparatus but is one specifically built in such a manner so as to conduct the present invention and related processes.

20 The systems of the present invention may also be performed in an apparatus capable of "dual mode" functions. A "dual mode" apparatus is one capable of both washing and drying fabrics within the same drum. These apparatus are commercially available, particularly in Europe.

25 An apparatus used to carry out the present invention will typically contain some type of control system. These include electrical systems, such as, the so-called smart control systems, as well as more traditional electro-mechanical systems. The control systems would enable the user to select the size of the fabric load to be cleaned, the type of soiling, the extent of the soiling, the time for the cleaning cycle. Alternatively, the user could use pre-set cleaning and/or refreshing cycles, or the apparatus could control the length of the cycle, based on any number of ascertainable parameters. This would be especially true for electrical control systems. For example, when the collection rate of lipophilic fluid reaches a steady rate the apparatus could turn its self off after a fixed period of time, or initiate another process for the lipophilic fluid.

In the case of electrical control systems, one option is to make the control device a so-called "smart device". This could mean including, but not limited to, self diagnostic system, load type and cycle selection, linking the machine to the Internet and allowing for the consumer to start the apparatus remotely, be informed when the apparatus has cleaned
5 a fabric article, or for the supplier to remotely diagnose problems if the apparatus should break down. Furthermore, if the system of the present invention is only a part of a cleaning system, the so called "smart system" could be communicating with the other cleaning devices which would be used to complete the remainder of the cleaning process, such as a washing machine, and a dryer.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
22